

# Directory Search Results

WRAS Approval Number: 2110365

Approved Product

Single hole, single outlet (swivel) combination tap assembly (stainless steel body - various finishes, see model), incorporating a ceramic cartridge headwork with a single lever operating member. The spout outlet incorporates a plastic aerator with an integral flow regulator. Maximum working pressure 10.0 bar. Maximum operating temperature 60°C.

- **Section:** 0470 Combination Tap Assemblies (?section=0470)
- **Section Subtitle:** Single hole, metal, single outlet, swivel. Taps used in high risk installations, such as kitchen sinks, are considered to be a fluid category 5 risk. Backflow protection is usually provided in the form of an AUK3 tap gap. Where an AUK3 tap gap cannot be maintained, for example where the tap gap is compromised as a result of:-
  - the tap being lowered in any way;
  - adjustment to the spout which reduces the distance between the tap outlet and spillover level of the sink;
  - or the operation of a pull out hose attachment; alternative fluid category 5 backflow protection is required.
- **WRAS Approval Number:** 2110365
- **Expiry date:** 31/10/2026
- **Size:** Stainless steel braided PEX lined flexible hose assemblies incorporating 3/8" captive nut end connections.
- **Marking:** QTOO (brand of D Line) on operating member.
- **Installation Requirements** R001 (/approvals/testing-requirements/installation\_requirements/irn\_r001)R006 (/approvals/testing-requirements/installation\_requirements/irn\_r006)R009 (/approvals/testing-requirements/installation\_requirements/irn\_r009)R010 (/approvals/testing-requirements/installation\_requirements/irn\_r010)
- **Model**  
QT1200xxx Tall single hole mixer.

Model added June 2022

QT2100xxx

Where xxx denotes the finish and can be replaced by 1 to 3 digits:

M = brushed stainless steel finish.

PP1 = polished PVD gunmetal finish.

- **Factor:** D Line View All Listings by this Company (?company=21390)