Sensor tap for wall


Qtoo collection

250mm infrared sensor tap for wall installation



QTOO collection, sensor tap for wall.

Manufactured in the highest quality marine grade, AISI 316 stainless steel, protecting against high levels of corrosion and securing cleaner drinking





Product specification Projection: 250mm - 9 27/32"

Rose Ø90mm - 3 1/2" with integrated sensor

Built in aerator

Max. flow rate: 5L - 1,3gpm Comfort time out 2 sec.

Security time out 30 sec.

Automatic rinse cycle (deactivated) Always secure min. 140mm - 5 1/2" distance from

aerator to washbasin waste


Use with Flexbox QSF01 and connecter QS3400 Temperature control in Flexbox

Max. work pressure 8 bar

Including 920mm - 36 7/32" cable

Lead free compliant Material: Marine grade AISI 316 stainless steel

20-year warranty (5 years for coated items)



Available finishes



Charcoal

Copper

Spare parts/ accessories

QSF01 - Premix Flexbox QS3400 - Built in spout connector

Mounting

https://dline.com/mounting-instructions/

Product care
dine products are produced in the highest quality marine grade AISI 316 stainless steel. To sustain the unique of line finish please follow the below instructions:

• Wash down the surfaces using scapy water or mid detergent
• Always thoroughly rinse off with clean water
• To complete the cleaning procedure dry/poish the surface with a soft dry cloth
Please do not use socuring powder, steel wood, chloride based detergents or other aggressive cleaning
products as these may damage the surface. It is not due to the stainless steel quality, but to impurities in the
environment, aggressive conditions or improper or insufficient cleaning.